

## Three-phase Residential On-grid Inverter



### X3-PRO G2

8kW/10kW/12kW/15kW  
17kW/20kW/25kW/30kW

**10 YEARS**  
WARRANTY  
★★★★★

#### High Efficiency



- ⚡ Built-in global MPP scan
- ⚡ 32A per MPP tracker
- ⚡ Up to 98.5% efficiency
- ⚡ 150% DC oversizing & 110% AC overloading output
- ⚡ Low startup voltage & ultra-wide MPPT range

#### Intelligent Design



- ⚡ Smart loads management (e.g., heat pump, smart EV charger)
- ⚡ Ultra-high power density
- ⚡ IP66 protection degree
- ⚡ 24h monitoring (WiFi/LAN/4G)

#### Flexible Adaptability



- ⚡ Built-in export power control function

#### Assured Safety



- ⚡ AFCI support (optional)\*
- ⚡ Type II SPD on AC&DC side

\* Feature to be upgraded in the future

PV INPUT								
Max. recommended PV array power	12.0 kWp	15.0 kWp	18.0 kWp	22.5 kWp	25.5 kWp	30.0 kWp	37.5 kWp	45.0 kWp
Max. PV input voltage <sup>①</sup>	1100 V							
Nominal PV input voltage	650 V							
Operating voltage range	135 ~ 985 V							
MPPT voltage range <sup>②</sup>	160 ~ 980 V							
Start-up voltage	200 V							
No. of MPP trackers / Strings per MPP tracker	2 / (2 / 2)						3 / (2 / 2 / 2)	
Max. input current per MPPT	32 A							
Max. input short circuit current per MPPT	40 A							
AC OUTPUT								
Rated output power	8 kW	10 kW <sup>③</sup>	12 kW	15 kW <sup>⑤</sup>	17 kW	20 kW	25 kW	30 kW <sup>⑥</sup>
Rated output current	12.2 A	15.2 A	18.2 A	22.8 A	25.8 A	30.3 A	37.9 A	45.5 A
Max. output apparent power	8.8 kVA	11.0 kVA <sup>④</sup>	13.2 kVA	16.5 kVA <sup>⑤</sup>	18.7 kVA	22.0 kVA	27.5 kVA	30.0 kVA <sup>⑥</sup>
Max. output continuous current	13.2 A	16.0 A	19.3 A	24.2 A	27.5 A	33.6 A	41.8 A	45.5 A
Nominal AC voltage	3 / N / PE, 220 / 380 V 3 / N / PE, 230 / 400 V							
Nominal AC frequency	50 Hz / 60 Hz							
AC frequency range <sup>③</sup>	50 ± 5 Hz / 60 ± 5 Hz							
Adjustable Power Factor range	~ 1 (0.8 lagging to 0.8 leading)							
THDi (rated power)	< 3%							
EFFICIENCY								
Max. efficiency	98.2%			98.3%			98.5%	
European efficiency	97.7%			97.8%			98.0%	
ENVIRONMENT LIMIT								
Ingress protection	IP66							
Operating ambient temperature range	-30 ~ 60°C							
Max. operating altitude	4000 m							
Relative humidity	0 ~ 100 % RH (condensing)							
Overvoltage Category	Mains: III / PV: II							
GENERAL								
Dimensions (W x H x D)	482 x 417 x 186 mm							
Net weight	24.5 kg			26.0 kg			28.0 kg	
Cooling concept	Nature cooling			Smart cooling				
Communication interfaces	RS485/DRM, Optional: Meter							
Power consumption (night)	< 3 W							
Topology	Non-isolated							
Certificates and approvals	VDE4105, EN 50549, AS 4777.2, IEC 61727, IEC 62116, IEC 61683, IEC 60068, EN 50530, NB/T 32004, IEC/EN 62109-1, IEC/EN 62109-2							
AC auxiliary power supply (APS)	Optional							
PROTECTION								
Protections	Over / under voltage protection, DC isolation protection, DC reverse-polarity protection, Grid monitoring, DC injection monitoring, Back feed current monitoring, Residual current detection, Over temperature protection, AC overcurrent protection, AC short-circuit protection							
Active anti-islanding method	Frequency shift							
Surge protection (DC / AC)	DC: Type II, AC: Type II							
Arc-fault circuit interrupter (AFCI)	Optional							

① The maximum input voltage is the upper limit of the DC voltage. Any higher input DC voltage would probably damage the inverter

② Input voltage exceeding the MPPT voltage range may trigger inverter protection

③ The AC frequency range may vary from different country codes

④ 9999 for AS4777.2

⑤ 14999 for AS4777.2

⑥ 29999 for AS4777.2